


HPX POSITION			
model HPX 020 TB		code H02000000004	
CONSTRUCTIVE FEATURINGS			
frame DOUBLE VANE 40mm ALUMINIUM PROFILE			
panels SANDWICH PANELS thick.42mm outside precoated inside galvanized sheet metal			
baseframe ALUMINIUM PROFILE		drain train INOX	
SUPPLY FAN			
model:	AT 9-7 S	flow rate:	2400 mc/h
T.S.P.:	840 Pa		pulley 2 SPZ 100
motor:	1.1kW 4poles IP55	voltage:	380/3/50 V/ph/Hz
			pulley 2 SPZ 140
			belt type: SPZ850
RETURN FAN			
model:	AT 9-7 S	flow rate:	2400 mc/h
T.S.P.:	665 Pa		pulley 2 SPZ 125
motor:	1.1kW 4poles IP55	voltage:	380/3/50 V/ph/Hz
			pulley 2 SPZ 150
			belt type: SPZ900
RIGID BAG FILTER			
model:	595X595X287 mm	class:	F7
model:	mm	class:	n°: 2
SYNTHETIC CELL FILTER			
model:	595X595X98 mm	class:	G4
model:	mm	class:	n°: 2

Disegnato	Data	Approvato	Data	Tolleranze generali di lavorazione non quotate UNI-ISO 2768m	Scala	UNI A3
Sturaro E.	04/10/2007				1:30.	⚠
				Denominazione		
				HPX 020 TB R. VORTVENT ORDINE VI004430-0316		
				Codice disegno	Rev.	
				H02000000004	0	