



HPX POSITION			
model HPX 040 TB	code H04000000013		
CONSTRUCTIVE FEATURINGS			
frame	DOUBLE VANE 40mm ALUMINIUM PROFILE		
panels	SANDWICH PANELS thick:42mM outside precoated inside stainless steel sheet metal		
baseframe	ALUMINIUM PROFILE		
drain tray	STAINLESS STEEL SHEET METAL		
SUPPLY FAN			
model:	AT 10-10 S	flow rate:	4300 mc/h
T.S.P.	790 Pa		pulley 2 SPZ 85 RPM 1682
motor	22kW 4poles IP55	voltage	380/3/50 V/ph/Hz
			pulley 2 SPZ 100 belt type: SPZ 737
RETURN FAN			
model:	AT 10-10 S	flow rate:	4300 mc/h
T.S.P.	790 Pa		pulley 2 SPZ 85 RPM 1682
motor	22kW 4poles IP55	voltage	380/3/50 V/ph/Hz
			pulley 2 SPZ 100 belt type: SPZ 737
RIGID BAG FILTER			
model:	595X595X292 mm	class:	F7
			n°: 2
model:	595X287X292 mm	class:	F7
			n°: 2
SYNTHETIC CELL FILTER			
model:	595x595x98 mm	class:	G4
			n°: 2
model:	595x287x98 mm	class:	G4
			n°: 2

Disegnato	Data	Approvato	Data	Tolleranze generali di lavorazione non quotate UNI-ISO 2768m	Scala	UNI A3
Bisognin L.	30/10/2007				1:30.	
				Denominazione		
				HPX 040 TB R. VORTVENT V1004454-031608 Codice disegno H04000000013		